



## HSEuireg04801 Lab Power Supply DIN-Rail, 2.6W/CUI free air

- 480W C/V programmable, Laboratory Power Supply scalable for test bench
- Multifunctional analogue Interface 0-5V/0-10V/0-20mA/4-20mA
- Real Time Monitoring

## HSEuireg04801

Model	HSEuireg04801						
Power	480W						
Nominal Input	115/230Vac select						
Input Range AC	90..115Vac/184..265Vac						
Input Range DC	250... 375Vdc						
Input Frequency	47... 63Hz						
Hold-Up Time	50ms						
Inrush Current Protection	9,8Aeff / 13,8Apeak active limiter ±6%						
Autostart	Soft start						
Programmable Output Voltage	0-18V	0-30V	0-50V	0-90V	0-130V	0-180V	0-240V
Programmable Output Current	0-40A	0-24A	0-15A	0-8A	0-5,5A	0-4A	0-3A
Ripple & Noise mVpp	40mV	40mV	100mV	150mV	200mV	300mV	400mV
Stability at Load Switch	±0,2%						
Transient Time	< 1ms						
Efficiency	90%						
Basic Load	Idling-proof						
Short Circuit Protection	Continuous						
Ambient Operating Temperature	-20°C... +70°C						
Cooling	Natural convection						
Temperature Monitoring	Yes						
Dimensions (WxHxD)	200x130x114,5mm						
IP-Range	IP20						
Safety IEC	EN60950-1 EN50178 EN60204-1						
Safety Class 1(A)	VDE0100 VDE0805						
Input to Output Isolation	3000Vac						
Climatic Class, Humidity	3k3, 95% non condensing						
EMI	EN55022B						
EMS	EN61000-6-2,3						
MTBF IEC61709	400000h						
Programming Interface Voltage	0... 5Vdc, 0... 10Vdc, 0-20mA, 4-20mA						
Programming Interface Current	0... 5Vdc, 0... 10Vdc, 0-20mA, 4-20mA						
Monitoring Interface Voltage	0... 5Vdc, 0... 10Vdc						
Monitoring Interface Current	0... 5Vdc, 0... 10Vdc						
Power Good Relay	Yes						
Sense Operation	Yes						
Remote Shutdown	Yes						
Reference Voltage	Yes						
Options	see data sheet						