



CPS-EC480 DIN-Rail Battery Charger & Industrial Precision Power

- C/V precisely adjustable
- Current Monitor Imon
- Perfect C/V chart with no Foldback
- Power Good Relay AC & DC
- Remote Shutdown
- Inhibit (Interlock) Function
- Sense
- Natural Cooling

□

CPS-EC480

Model	CPS-EC480								
Power	480W								
Nominal AC Input	115/230Vac								
Input Range AC	90..115Vac/186..265Vac								
Input Range DC	250... 375Vdc								
Input Frequency	47... 63Hz								
Hold-Up Time	50ms								
Inrush Current	Electronic Inrush Current Limiter 9,8Arms								
Autostart	Soft start 100ms								
Output Voltage	24V	36V	48V	60V	72V	110V	150V	220V	300V
Output Current	20A	13,3A	10A	8A	6,7A	4,4A	3,2A	2,2A	1,6A
DC Voltage Setting	24-30V	36-45V	48-58V	60-75V	72-90V	110-137,5V	132-180V	220-264V	264-360V
DC Current Setting	10-21A	6,6-14A	5-10,5A	4-8,4A	3,4-7A	2,2-4,6A	1,6-3,3A	1,1-2,3A	0,8-1,7A
Ripple & Noise mVpp	40mV	40mV	100mV	150mV	200mV	300mV	400mV	400mV	400mV
Load Regulation	±0,05% 0-100%								
Load Change	Response < 1ms 10-100% 100-10%								
Efficiency	up to 92%								
Base load	non, continuous open circuit proof								
Short Circuit Protection	Continuous								
Ambient Temperature	-20°C... +70°C Operation								
Cooling	natural cooling								
Temperature Control	Yes								
Dimensions	(WxHxD) 200x130x114,5mm IP20								
Safety IEC	EN60950-1 EN50178 EN60204-1								
Safety Class 1(A)	VDE0100 VDE0805								
Input/Output Isolation	3000Vac								
Climatic Class, Humidity	3k3, 95% non condensing								
EMI/EMS	EN55022B / EN61000-6-2,3								
EMS	EN61000-6-2,3								
MTBF / MTTF IEC61709	400000h / 148312h								
Power Good Relay	AC & DC low voltage detection, isolated								
Features	Current-Monitoring, External Shutdown, Inhibit (Interlock), Sense Compensation								
Options	Protective Coating, Baseplate cooler for hardmount								